



# SUPERFLEX®

MS173  
PURPLE RAIN

MS172  
BLUE SKY

MS113  
CHARCOAL

MS123  
WHISPER GREY

MS183  
SANDALWOOD

MS176  
PRUSSIAN BLUE

MS162  
HERB GREEN

MS164  
FENNEL

MS142  
FIERY RED

MS122  
ASH GREY

MS157  
BURNT ORANGE

MS153  
CITRUS

MS181  
BONE

MS185  
HAZELNUT

MS145  
TEAL

Fully-flexible vinyl floor sheeting and tiles available in 2 gauges and a range of standard colours. Superflex® combines a distinctive yet forgiving marble effect with high standards of performance in terms of durability.

## WARRANTY

FloorworX offers a 15 year limited warranty, subject to our terms and conditions, against defective material provided that it is installed and maintained in accordance with our recommendations.



# SUPERFLEX®



## TOTAL THICKNESS

2.00mm  
2.50mm



## DIMENSIONS

**Tiles** 2.00mm : 300mm x 300mm

**Rolls** 2.00mm : 1.2m x 15LM

2.50mm : 1.2m x 15LM



**Welding Rod** : Ø 4.30mm x 50LM



## PACKAGING

**Tiles** 2.00mm : 50 Tiles Per Box (4.5m<sup>2</sup>)

**Rolls** 2.00mm : 18m<sup>2</sup> Per Roll

2.50mm : 18m<sup>2</sup> Per Roll

**Welding Rod** : 50LM Rolls



## TOTAL WEIGHT

2.00mm : 3.75kg/m<sup>2</sup>

2.50mm : 4.50kg/m<sup>2</sup>



## COLOUR RANGE

16 Selected Colours

**NOTE:** Samples are cut from various areas of a tile or sheet, these are representative samples. For technical reasons the material may vary in shade and appearance. Please ensure you view a full tile or piece, or visit our website to see the marble pattern.



**LOCAL CONTENT: 75,3%**



**FLOORWORX**  
INSPIRED BY SOUTH AFRICA

## Unique Selling Points

- Product is Fully-Flexible – the product can be taken (covered) up a wall or dressed around an internal/external corner, window or door reveal.
- Local manufacture
- Brand reputation – in the market for over 70 years
- Low carbon footprint
- Durable – dense, smooth finish and proven performance in the market
- Sans mark – SABS 786
- Composition – 62% natural
- 100% recyclable
- Surface Finish – Contrasting two-tone marbling (pattern) which is throughout the total thickness of the product.
- Uncoated surface finish, making it easy to carry out remedial work if necessary
- Phthalate-free / No restricted substances (Phthalates/Formaldehyde/Heavy Metals)
- Not directly dependent on ROE
- Class-1 Fire Rating
- Continuity of supply
- Distribution capability - service level to market
- Direct delivery to the site
- Product can be hot seam-welded, creating an impervious surface finish
- Matching welding rod for hot seam welding
- Abrasion rating - M
- Wear Layer Binder Content – Type III
- Representation (National footprint)
- Technical support/backup