

DATA SHEET

FLOOR PRIMER

Revision Date
DECEMBER 2018



Modified Latex Liquid Primer for Porous Surfaces

Description

TAL Floor Primer is a modified latex liquid primer designed for use on porous surfaces, ensuring a good bond onto the substrate.

TAL Floor Primer is compatible with TAL Superscreed, TAL Screedmaster and TAL Superscreed SL Underlayment Compounds.

It is also used as a primer prior to the application of TAL Superflex and TAL Sureproof Waterproofing Compounds.

TAL Floor Primer can also be used as a primer onto very porous substrates, such as brickwork, prior to tiling.

Note : This product is designed for the above-mentioned application only. TAL will not be liable for misuse or adulteration of the product.

Laboratory Test Data

Type	Latex Primer
Colour	Milky White
Application Temperature Range (Ambient)	+ 10°C - +30°C
Density	1.01
Pack Size	5L, 25L, 200L

Volatile Organic Content

VOC = <10 g/L

Packaging

TAL Floor Primer is available in 5L and 25L bottles, and 200L returnable drums.

Coverage

Approximately 4 - 5m² / 1L (per coat), depending on surface porosity.

Storage & Shelf Life :

Ensure lid is tightly sealed and packaging is secure and upright.

Secure product when transporting to prevent accidental spillage.

When stored in original sealed packaging in dry internal conditions between 10°C and 30°C and out of direct sunlight the product has a shelf life of 6 months from date of manufacture.

Never store directly on a concrete floor.

Installation / Health & Safety

This product is for industrial use only by trained operatives. It is potentially hazardous if not used correctly.

Please refer to the Method Statement (MS) and Material Safety Data Sheet (MSDS) prior to the purchase and use of this product.

Product Guarantee :

TAL products are manufactured and tested in accordance with TAL procedures, which are maintained in line with Quality Control System Standard ISO 9001 : 2015, OSHAS 18001:2007 and Environmental Management System ISO 14001:2015. TAL products are guaranteed to be free from manufacturing defects and fit for design purposes.

TAL warrants the technical properties of their materials when used strictly in accordance with their materials and methods specifications for the particular project, and where the prescribed standard of workmanship is followed. However, we have no influence over specific site conditions and therefore, if in doubt, the user must always carry out sufficient tests to satisfy himself/herself that the product is suitable for the intended purpose. In special cases, obtain professional advice.

TAL shall not be liable for the standard of workmanship on site, or for any defects or damage due to external causes or factors beyond the control of TAL including, without limitation, unsound structures or foundations, building movement (cracking, creep, deflection, vibration, etc), design defects, earth tremor or other seismic disturbances, land slip, fire, flood or other immersion, or any products which have been adulterated, contaminated or misused in any way. The aforementioned list is not exhaustive.

NOTE : we require timeous notification, ***in writing***, of an alleged defect and the opportunity to assess and investigate the problem to our satisfaction ***prior*** to any remedial work whatsoever being carried out.

TAL Technical Advice Centre

For advice or a detailed Materials and Methods Specification contact the TAL Technical Advice Centre on 0860 000 TAL(825), or e-mail taltech@tal.co.za.

Branches : Gauteng (011) 206-9700;

Cape (021) 386-1810; Natal (031) 579-2263

Important Notice:

TAL believes the information on this sheet to be correct – but does not guarantee its accuracy or completeness. Conduct your own tests of this product to determine its suitability for intended use. User assumes all risks and liability during testing and use of this product. In special cases, obtain professional advice. The only obligation of TAL shall be to replace any of this product proved to be defective in material. TAL shall not be liable for any injury, loss or damage, direct or consequential, relating to the use or inability to use this product. Except as expressly provided above, all products sold and samples furnished without any warranty of merchantability or any other warranty, express or implied. TAL reserves the right to change the information on this datasheet. Please contact the TAL Technical Advice Centre on taltech@tal.co.za, or 0860 000 825 to ensure you have the latest version.